



The Public Health and Safety Organization

NSF Product and Service Listings

These NSF Official Listings are current as of **Tuesday, November 25, 2025** at 12:15 a.m. Eastern Time. Please [contact NSF](#) to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information:

<http://info.nsf.org/Certified/food/Listings.asp?Company=C0070221&>

NSF/ANSI 2 Food Equipment

LEDingEDGE Lighting, Inc.

600 North Bullard Avenue

Suite 4

Goodyear, AZ 85338

United States

805-383-8493

[Visit this company's website](#)

(<http://www.ledingedge.com>)

Facility : Angola, IN

Lighting Approved for Food Zone (Non-Contact), Splash, and Non-Food Zones

Premium[2]

MICPRM(1)(2)-(3)V-(4)-(5)K-(6)

MINPRM(1)(2)-(3)V-(4)-(5)K-(6)

[2] (1) Two to three numerical digits representing number of LEDs on fixture

(2) Two to three numerical digits representing mA

(3) Two numerical digits indicating volts

- (4) Two numerical digits indicating length in inches up to 96"
- (5) Two numerical digits indicating color options in Kelvin color
- (6) C (clear lens) or F (frosted lens)

Micro-Mini ORION[1]

MIC(1)-T-(2)-(3)-(4)-(5)-(6)-(7)

[1] (1) Four numerical digits representing brightness.

Ex: 3250, 1665, 1650

- (2) Indicates voltage: 12V or 24V
- (3) Two numerical digits indicating length in inches up to 96"
- (4) Code indicating LED color option: 27K, 30K, 35K, 40K or 50K
- (5) Indicates type of Lens: F - Frosted, C - Clear
- (6) May or may not include optional suffix indicating end cap type
- (7) May or may not include optional suffix indicating on/off touch switch/dimmer.

Mini-ORION[1]

MIN(1)-T-(2)-(3)-(4)-(5)(6)-(7)

[1] (1) Four numerical digits representing brightness.

Ex: 3250, 1665, 1650

- (2) Indicates voltage: 12V or 24V
- (3) Two numerical digits indicating length in inches up to 96"
- (4) Code indicating LED color option: 27K, 30K, 35K, 40K or 50K
- (5) Indicates type of Lens: F - Frosted, C - Clear
- (6) May or may not include optional suffix indicating end cap type
- (7) May or may not include optional suffix indicating on/off touch switch/dimmer.

COMPONENTS:**Cord Grips for Food Zone (Non-Contact)**

O-BRK-MIN-CG-2

Cord Grips for Food Zone Non-Contact

O-BRK-MIC-CG-2

O-BRK-MIC-CG-20

Cord Grips for Food Zone (Non-Contact)

O-BRK-MIN-CG-20

Micro-Mini ORION Bracket

Custom 1 O-BRK-MICRO-MIN-P-AR-20

Custom 2 O-BRK-MICO-MIN-P-VHB-2

Custom 2 O-BRK-MICO-MIN-P-VHB-20

Micro-Mini ORION Bracket Polycarbonate

O-BRK-MICRO-MIN-P-2

O-BRK-MICRO-MIN-P-20

Micro-Mini ORION Bracket Magnet

O-BRK-MICRO-MIN-P-MAG-2

O-BRK-MICRO-MIN-P-MAG-20

Micro-Mini ORION Bracket Rotating

O-BRK-MICRO-MIN-R1-2

O-BRK-MICRO-MIN-R1-20

O-BRK-MICRO-MIN-R1-VHB-2

O-BRK-MICRO-MIN-R1-VHB-20

Mini ORION Bracket Magnet

O-BRK-MIN-P-MAG-2

O-BRK-MIN-P-MAG-20

Mini ORION Bracket Metal

O-BRK-MIN-M-2

O-BRK-MIN-M-20

Mini ORION Bracket Polycarbonate

O-BRK-MIN-P-2

O-BRK-MIN-P-20

Mini ORION Bracket Rotating

O-BRK-MIN-R1-2

O-BRK-MIN-R1-20

TIPS "Twist-In Power System" for Splash and Non-Food Zones[3]

TIPG-4-(1)

TIPG-6-(1)

[3] (1) B or W suffix indicating color, black or white.

TIJ "Twist-In Jumpers" for Splash and Non-Food Zones[4]

TIJ-(1)-(2)-(3)-M

[4] (1) Indicates length in inches: 18, 24, 30

(2) Indicates color:

B - Black, W - White

(3) Indicates wire end:

SE - Straight End

ST - Striped End

Jumper Cords for Splash and Non-Food Zone[5]

J - (1) - (2) - (3) - HT

[5] (1) Indicates length in inches: 3, 6, 9, 12, 18, 24, 36, 48, 60, 72, 96, and 120

(2) Indicates color: B - Black, W - White

(3) Indicates wire end:

ST-ST - Straight End - Straight End

ST-SE - Straight End - Stripped End

RA-RA - Right Angle End-Right Angle End

RA-SE - Right Angle End-Stripped End

Number of matching Manufacturers is 1

Number of matching Products is 31

Processing time was 0 seconds