

## Specifications:

**Description:** This luminaire “Center Column” glass door lighting is ideal for refrigerated or freezer display case lighting applications. The “center column” mullion is designed to mount onto the center door frame and projects the light beam two opposite directions illuminating the products on both the right and left sides of the glass doors.

**Features:**

**Lighting:** Solid state lighting (SSL) LEDs; surface mounted device (SMD) populated onto a printed 2 layer, 2oz FR4 circuit board (PCB)

**Tube and endcaps:** polycarbonate LEXAN 244R

**LED Driver Input:** 100 VAC to 277 VAC; use only Cass 2 UL listed or UL recognized LED driver

**LED Driver Output:** 12 or 24 VDC

**Light Beams:** Can be ordered to project light at 15° or 30°; use 15° when products are 6” or closer to the door; use 30° when products are over 6” away from the door

**Temperature Ratings:** PCB (LEDs, etc): Ambient: -25°C~45°C; Case: -25°C~70°C; UL 2108 testing: 25°C

**Life:** Long life with L70 > 50,000hrs

**Warranty:** 5 year limited warranty from manufacturing defects

**Safety:** All our luminaires are UL/cUL Listed

**Certifications:** ISO 9001:2015 certified

## Mullion Super Bright Center Column Glass Door Lighting

Two different LED boards in the same tube projecting two different light directions



## Wattage and Lumens:

**Super Bright 3250 model:**

Length	Wattage	Lumens
25"	5 W	1356 lm
47"	10 W	2712 lm
58"	12.6 W	3396 lm
69"	15 W	4076 lm

**General Purpose 1665 model:**

Length	Wattage	Lumens
25"	3.28 W	914 lm
47"	6.56 W	1828 lm
58"	8.20 W	2286 lm
69"	9.84 W	2742 lm

\*Lumens are estimates and are based on 24V, 40K PCB, clear lens  
 \*Please note that additional lengths are available in 12V  
 \*Wattage usage is same for 12V and 24V

## UL Test Data:

Our custom-built mullion light series has 512 variations that affect performance data. Please see call us at 623-248-6232 and talk to one of technicians for UL electrical, integrating sphere and distribution data.

## How To Create a Part Number:

Series	Voltage options	Length Options	Color (CCT) options	Lens Options	Projection of Light angle options
MM2R-3250 Or MM2R-1665	12V or 24V	25", 47", 58" or 69"	30K 35K 40K 50K	Clear (C) or Frosted (F)	15° or 30°

**Example part number:** MM2R-3250-12V-47-40K-L-F-15

## Options:

**Brightness:** General Purpose or Super Bright  
**Voltage:** 12 or 24 VDC  
**Length:** 25", 47", 58" or 69"; additional lengths available for 12V model  
**Color:** Standard CCTs choices are 3000K, 3500K, 4000K, and 5000K with a CRI >90  
**Lens / Tube:** Clear or frosted  
**Projection of Light:** 15 or 30°

## Accessories:

**Brackets:** See next page  
**Drivers:** See Driver Spec Sheet  
**Jumpers:** See next page  
**Harnesses:** See next page



## Brackets:

**Feature:** Metal snap-in or Polycarbonate LEXAN 244R snap-in

**Ordering Tips:**

Order in quantities of 2 for a smaller single luminaires or 20 for larger projects.

We recommend our brackets are used 4-6" from each end for luminaires 24" or shorter; also one every 24" for longer luminaires.

**Brackets Part Numbers:**

Description	Quantity	Part Number
Metal	2 20	O-BRK-MIN-M-2 O-BRK-MIN-M-20
Polycarbonate	2 20	O-BRK-MIN-P-2 O-BRK-MIN-P-20



## Jumpers:

**Features:**

Polarized for direct 12v or 24v DC power supply

18/2 AWG (18 gauge wire / 2 wires parallel)

Wire rated at 105 °C ; Molded ends are rated at 90°C


Available in black

Available in lengths: 5" , 24" , 36" and 48"

Jumpers come in the following variations: Female / Male; Female / Stripped; Male / Stripped

**Jumpers Part Numbers:**

Part Number	Description	Length	Color
M-J-05-F-SE-P	5" Jumper, Female, Striped End, Polarized	5"	Black
M-J-05-M-SE-P	5" Jumper, Male, Striped End, Polarized	5"	Black
M-J-24-F-SE-P	24" Jumper, Female, Striped End, Polarized	24"	Black
M-J-24-M-SE-P	24" Jumper, Male, Striped End, Polarized	24"	Black
M-J-36-F-M-P	36" Jumper, Female, Male, Polarized	36"	Black
M-J-48-F-M-P	48 Jumper, Female, Male, Polarized	48"	Black
M-J-48-F-SE-P	48" Jumper, Female, Striped End, Polarized	48"	Black



## Harnesses :

**Features:**

Polarized for direct 12v or 24v DC power supply

18/2 AWG (18 gauge wire / 2 wires parallel)

Wire rated at 105 °C ; Molded ends are rated at 90°C

Available in black

Available in lengths: 5" , 24" , 36" and 48"

**Harnesses Part Numbers:**

Kit Part Number	Description	Length	Color
MMH-1D-1R-1L	One MMH-36-2F-1M-P + One M-J-36-F-M-P	36"	Black
MMH-2D-1R-1L	Two MMH-36-2F-1M-P + One M-J-36-F-M-P	36"	Black
MMH-2D-1C-1R-1L	Three MMH-36-2F-1M-P + One M-J-36-F-M-P	36"	Black
MMH-3D-2C-1R-1L	Four MMH-36-2F-1M-P + One M-J-36-F-M-P	36"	Black
MMH-4D-3C-1R-1L	Five MMH-36-2F-1M-P + One M-J-36-F-M-P	36"	Black
MMH-5D-4C-1R-1L	Six MMH-36-2F-1M-P + One M-J-36-F-M-P	36"	Black

